



भारतीय प्रौद्योगिकी संस्थान हैदराबाद  
Indian Institute of Technology Hyderabad

**Indian Institute of Technology Hyderabad**  
Kandi- 502 285, Sangareddy, Telangana State, India  
Phone: 040 2301 6018: Fax: 040 2301 6032  
Email: [stores@iith.ac.in](mailto:stores@iith.ac.in)

Date: 21 Mar 2018

**CORRIGENDUM – 2**

1. It is notified to all the concerned parties that with reference to our Tender No. IITH/5(7)/NEEL/2017/T205 dated 20.02.2018 for supply of "PROJECTOR FOR PROJECTION MAPPING", the following changes are being made w.r.t. the Tender: -

- (i) **Revised Specifications – As per ANNEXURE (01 page) to this corrigendum.**
- (ii) **Revised Due Date & Time for Submission of Tenders is as below: -**

	EXISTING	AMENDED AS
Last Date & Time for submission of Tender	27 Mar 2018 by 03.00 pm	04 Apr 2018 by 03.00 pm
Date & Time of Tender Opening	27 Mar 2018 by 03.30 pm	04 Apr 2018 by 03.30 pm

2. If any of you have already submitted your bid prior to issue of this corrigendum you are required to re-submit your bid before the revised Due Date & Time, considering changes in the specifications of the Tender as per this **Corrigendum-2**.

3. All other Terms & Conditions of Tender remain completely unchanged.

Yours faithfully,

**(V. Venkat Rao)**  
Joint Registrar

PROJECTOR FOR PROJECTION MAPPING

Sr No	Features	Description
1	Projection system	3 LCD or DLP, 3 Chip technology
2	Projection mounting	Front / rear / ceiling
3	Pixel number	2,304,000 (1920 x 1200) x 3
4	Native resolution	1920 x 1200 (wuxga) with 4k enhancement
5	Aspect Ratio	4:3, 16:9, 16:10 and any additional ratios
6	Color brightness	20000 lumens or more
7	Contrast ratio	2,500,000: 1 absolute black; full white 20000 lm / full black 0 lm
8	Brightness uniformity	80% or more
9	Color reproduction	upto 1 billion colors
10	Lens shifts (horizontal and vertical)	at least +/- 30%
11	Keystone correction	at least +/- 30%
13	Light source life	At least 15,000 hours
14	Projection lens	Short throw, Medium throw and Long throw
15	Operating temperature	5 deg C to 45 deg C
16	power supply voltage	200-240v +/- 10%, 50/60 Hz AC
17	Fan noise	around 50 db normal mode
18	Interfaces	Should have: 1 X DVI-D, 1 X HDMI, 1 X HD BASE, Optional: 5-BNC, 1 X VGA, 1 X 3G-SDI
19	Audio in	mini stereo
20	Variable audio out	mini stereo
21	USB 2.0 connectors	type B, type A (for wireless)
22	Monitor out	mini D-sub 15 pin
23	Serial control	at least Rs 232 c, or later versions
24	SDI out	1
25	Video formats	NTSC, PAL, and others
27	Warranty	3 years